

## TRADE ENQUIRY FORM

Enquiry please quote	Date Required
Contact Details	Trickle vent in sash NOT to building regs
Ordered By	
Company Name	
Address	Outername - weided as standard
Postcode	Mechanical assembled Mechanical kit form
Tel	
Email	
Order No.	
Your Reference	
Delivery Date Requested	
Site Contact	Sash
Company Name	Decorative sasm with 20mm ovoid bead Chamilered sasm
Delivery Address	Bead - chamfered sash optionsh
Postcode	28mm chamfered bead
Tel	28mm ovolo bead
	— Charles de la Charles de Charles
Configuration – viewed from outside Please indicate sliding panel with an X	Standard profile colours (foils)  White (standard gloss not foiled)
Please indicate sliding panel with an X	Golden Oak Golden Oak on White
Internal slider External slider	Rosewood (black cherry) Rosewood (black cherry) on White
	White Woodgrain Black on White
	Anthracite grey on White (chamfered sash)
	Cream Cream on White
	Recommended extras
	PAS24 (internal slider only)
	Shootbolts (2 and 3 pane only)
·	Meeting style security bolts (2 pane internal sliders only)
Overall width mm (incl cill and add-ons)	Handles - 10 year Warranty
Overall frame height mm (incl cill and add-ons)	White Gold Black
	Chrome Grey Satin
Cill requirements (all cills 30mm upstand)	Handle Blanking Plate (finish to match handle)
95mm cill 150mm cill	— Letterbox
180mm cill No cill required	White Polished Gold Black Chrome
Night Vent (1 x 5000mm³ in add-on) (2 required for Scotland)	Glazing
30mm add-on 45mm add-on	4/20/4 toughened, low E, argon, black warm edge spacer bar
White Brown Tan	Double Glazed Unglazed
Grey/White Brown/White Tan/White	Glazing packer set  We manufacture our products in line with GGF guidelines, please see
	we manufacture our products in line with GGP guidelines, please see website for more information.
Weathered low threshold (internal slider only)	
	Door has to comply with Document Q of the Building Regulations (additional costs apply for the PAS 24 specification product)
Room divider Not weathered - 9mm	
Standard Threshold Fully weathered - 58mm	Keyed Alike Note: 3 star cylinder fitted as standard