Sash & Case Windows - Trade Quote Form

authentic collection sash windows

Company:

Your reference: **Your order no.:**

Page: **of**

Window Specification (Please tick required fields)

Sprayed:
- Internal ☐
- External ☐

(Foiled windows only)

Colour:

Finish:
- PVC-U White ☐
- White Foil ☐
- Cream Foil ☐

Build Method:
- Timberweld® ☐
- Mitred Option ☐

Continuous Horns:
- Yes ☐
- No ☐

Bottom Rail:
- 105mm Deep ☐
- 63mm Large ☐

Spacer Bar:
- White ☐
- Black ☐
- Grey ☐

Furniture Colour:
- Gold ☐
- Chrome ☐
- White ☐
- Bronze ☐
- Satin Chrome ☐

Limit Stops:
- Yes ☐
- No ☐

Fixing Lugs:
- Yes ☐
- No ☐

Timberweld® / Mechanical Joints to all corners as standard, Mitred Joints optional

Please identify any Georgian designs, toughened glass, laminated glass, obscured glass (providing pattern) & fixed sashes



Quantity					
Location					
Manufacture Width					
Manufacture Height					
Transom Drop					
Trickle Vent Placement	No ☐ Frame ☐ Sash ☐ Frame & Concealer ☐				
EA Requirement	mm²	mm²	mm²	mm²	mm²
Projecting Cill	No ☐ 85 ☐ 120 ☐ 150 ☐ 180 ☐ 225 ☐				
Egress Compliance	No ☐ Yes ☐				

Please identify any Georgian designs, toughened glass, laminated glass, obscured glass (providing pattern) & fixed sashes



Quantity					
Location					
Manufacture Width					
Manufacture Height					
Transom Drop					
Trickle Vent Placement	No ☐ Frame ☐ Sash ☐ Frame & Concealer ☐				
EA Requirement	mm²	mm²	mm²	mm²	mm²
Projecting Cill	No ☐ 85 ☐ 120 ☐ 150 ☐ 180 ☐ 225 ☐				
Egress Compliance	No ☐ Yes ☐				

Additional Notes:

Authentic: 147mm outerframe, Chamfered 'putty line' external and Ovolo 'sculptured' internal, tilt rests applied up to 35kg sash weight, Deep Bottom Rail, 4/16/4 Low 'E' & Low Iron glazing, Georgian where requested will be plant-on bar. Energy BFRC "A" rated and CE mark compliant as standard. PAS24/SBD BS7950 as standard. Furnished window frames over 916mm wide and/or with a central vertical Georgian bar will be fitted with 2 cam catches and keeps for security and balance. All sizes to be overall manufacture sizes and include cills and packers.

All windows viewed externally.

Sash & Case Windows - Trade Quote Form

authentic collection sash windows

Company:

Your reference: **Your order no.:**

Page: **of**

Window Specification (Please tick required fields)

Sprayed:
- Internal ☐
- External ☐

(Foiled windows only)

Colour:

Finish:
- PVC-U White ☐
- White Foil ☐
- Cream Foil ☐

Build Method:
- Timberweld® ☐
- Mitred Option ☐

Continuous Horns:
- Yes ☐
- No ☐

Bottom Rail:
- 105mm Deep ☐
- 63mm Large ☐

Spacer Bar:
- White ☐
- Black ☐
- Grey ☐






Furniture Colour:
- Gold ☐
- Chrome ☐
- White ☐
- Bronze ☐
- Satin Chrome ☐

Limit Stops:
- Yes ☐
- No ☐

Fixing Lugs:
- Yes ☐
- No ☐




Timberweld® / Mechanical Joints to all corners as standard, Mitred Joints optional

Please identify any Georgian designs, toughened glass, laminated glass, obscured glass (providing pattern) & fixed sashes

Quantity					
Location					
Manufacture Width					
Manufacture Height					
Transom Drop					
Trickle Vent Placement	No ☐ Frame ☐ Sash ☐ Frame & Concealer ☐				
EA Requirement	mm²				
Projecting Cill	No ☐ 85 ☐ 120 ☐ 150 ☐ 180 ☐ 225 ☐				
Egress Compliance	No ☐ Yes ☐				

Please identify any Georgian designs, toughened glass, laminated glass, obscured glass (providing pattern) & fixed sashes

Quantity			
Location			
Manufacture Width			
Manufacture Height			
Transom Drop			
Trickle Vent Placement	No ☐ Frame ☐ Sash ☐ Frame & Concealer ☐		
EA Requirement	mm²		
Projecting Cill	No ☐ 85 ☐ 120 ☐ 150 ☐ 180 ☐ 225 ☐		
Egress Compliance	No ☐ Yes ☐		

Additional Notes:

Authentic: 147mm outerframe, Chamfered 'putty line' external and Ovolo 'sculptured' internal, tilt rests applied up to 35kg sash weight, Deep Bottom Rail, 4/16/4 Low 'E' & Low Iron glazing, Georgian where requested will be plant-on bar. Energy BFRC "A" rated and CE mark compliant as standard. PAS24/SBD BS7950 as standard. Furnished window frames over 916mm wide and/or with a central vertical Georgian bar will be fitted with 2 cam catches and keeps for security and balance. All sizes to be overall manufacture sizes and include cills and packers.

All windows viewed externally.